



NOTES:

1. SLURRY SEAL COAT TREATMENT SHALL BE APPLIED AT LOCATIONS WITHIN COUNTY OF PLACER RIGHT-OF-WAY ONLY.
2. IF  $X < 3$  FT. FOR ALL TRENCHES REPAVE TO EDGE OF PAVEMENT. IF  $X < 5$  FT. SEAL TO EDGE OF PAVEMENT.
3. PAVEMENT SAWCUT SHALL BE LOCATED OUTSIDE OF VEHICLE WHEEL PATH.

MAIN DIAMETER	MINIMUM TRENCH WIDTH
4"	18"
6"	24"
8"	24"
10"	30"
12"	30"



## 4" THROUGH 12" TRENCH DETAIL - PAVEMENT

CITRUS HEIGHTS WATER DISTRICT

APPROVED BY: *Robert A. Chumbley* DATE: *5/8/13*  
 CITRUS HEIGHTS WATER DISTRICT

DRAWN: 8 MAY 2013  
 REVISED:  
 SCALE: N.T.S.  
 DESIGN: P.A.D.  
 CAD FILE: TREN\_713PC.DWG  
 PAGE: **TREN 713PC**

FOR CONSTRUCTION IN THE COUNTY OF PLACER