

CARSON 1220-48 "T" TYPE LID:

SHALL INCLUDE STRAIGHT TYPE HEXAGON
LOCK-DOWN BOLT (1) AND TOUCH READ HOLE.
SHALL BE MARKED "WATER"

CHRISTY FL36P RECESSED LID:

SHALL INCLUDE STRAIGHT TYPE PENTAHEAD
LOCK-DOWN BOLTS (2) AND NEPTUNE OFFSET
AMR HOLE, SHALL BE MARKED "WATER"

METER YOKE:
FORD, JONES, MUELLER, McDONALD

1	1 1/2" BRONZE SADDLE - IPT	11	1 1/2" WATER METER (BY DISTRICT)		
2	1 1/2" CORPORATION STOP - FULL-PORT BALL, MIP x CTS COMP	12	1 1/2" METE	R FLANGES AND IDLE	R (BY CONTRACTOR)
3	1 1/2" COPPER TUBING - TYPE K SOFT	13	1 1/2" × 18"	PVC NIPPLE - SCH 80	(BRASS IF BACKFLOW)
4	1 1/2" BRASS STREET ELBOW - CTS COMP x MIP	14	1 1/2" PVC COUPLING - SCH 80		
5	1 1/2" BRASS STREET ELBOW			NON-TRAFFIC AREAS	TRAFFIC AREAS
6	1 1/2" VALVE - FULL-PORT BALL, FIP x FIP or CTS COMP x FIP	15	METER BOX	CARSON 1730-15	CHRISTY FL36TBOX12
7	1 1/2" BRASS or COPPER (AS NECESSARY TO ADJUST TO	16	LID	CARSON 1730-4B	CHRISTY FL36P
	PROPER GRADE)	17	2" x 6" PRESSURE TREATED DOUGLAS FIR SUPPORTS (2)		
8	1 1/2" BRASS UNION	18	3/4" CLEAN CRUSHED ROCK		
9	1 1/2" × CLOSE BRASS NIPPLE	19	#2 WASHED SAND COMPACTED TO 90%		
10	1 1/2" COPPER/BRASS METER YOKE - 12"				
	w/2 FULL-PORT ANGLE BALL VALVES				
	INCLUDING PADLOCK WINGS ON INLET AND DUTLET				



CITRUS HEIGHTS WATER

## 1 1/2" COPPER WATER SERVICE - 1 1/2" WATER METER NEW CONSTRUCTION

CITRUS HEIGHTS	DRAWN: 25 SEP 2014	
CITROSTILIGITIS	REVISED: 15 APR 2021	
APPROVED BY:		SCALE: N.T.S.
melina Rieri	DATE:APRIL 15, 2021	DESIGN: P.A.D.
CITRUS HEIGHTS WATER DISTRICT		CAD FILE: WS_150CU.DWG
		WS_150CU